

UPM Raflatac

RECYCLASS TECHNOLOGY APPROVAL

Brussels, 6 December 2024

DISCLAIMER

RecyClass recognition applies only to UPM Raflatac 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology reported in Annex I. The recyclability assessment therefore does not refer to the testing of a specific packaging using this adhesive. Any specific packaging using this adhesive would need to be tested individually to demonstrate that the system of resin, adjuvants, label, closure, and printing conforms to the RecyClass Recyclability Evaluation Protocol for PE films, and that it is sorted in the PE flexible stream at the state-of-art sorting plants in Europe.

Publication of results of testing of this technology MUST clearly include all the conditions listed in the approval letter. Partial reporting of the conditions is forbidden.

Additionally, any change in the formulation of the technology must be communicated to the Technical Committee which will reassess the approval of the technology.

The RecyClass PO films Technical Committee was requested to carry out an assessment of the technology 'RP37 MULTIPURPOSE ACRYLIC EMULSION' by UPM Raflatac to verify its impact on the quality of recycled PE flexible packaging.

The technology is an unprinted pressure sensitive label (PSL) made of clear or white PE facestock representing 15 % of the film surface and a multipurpose acrylic emulsion pressure sensitive adhesive placed on a PE film. The adhesive represents 3.5 wt% of the total weight of the packaging while the PE facestock of the label represents 30 wt% of the total weight of the packaging.

According to the results that were obtained from the laboratory test by Plastics Forming Enterprises (PFE), carried out as per the Recyclability Evaluation Protocol for PE films (version 5.0), the 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology is fully compatible with coloured PE flexibles recycling.

Based on these results, RecyClass acknowledges that UPM Raflatac 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology will have no impact on the current European coloured PE flexibles recycling provided that PE flexible films using this technology are designed only under the following conditions¹:

- a) The density of the PE label is below 0.97 g/cm³;

¹ PE films designed under conditions other than those indicated need to be tested to assess their compliance with Recyclclass Recyclability Evaluation Protocol for PE films.

- b) The facestock of the pressure sensitive label applied on the packaging is made of clear or white PE, and represents 30 wt% of the total weight of the packaging, or less;
- c) The amount of multipurpose acrylic emulsion adhesive represents 3.5 wt% of the total weight of the packaging, or less;
- d) Any additional components, such as closure system are made of PE, preferably clear or white;
- e) Any additional component or features (inks, adhesives, ...) of the packaging must be compliant with the corresponding RecyClass Design for Recycling Guidelines².

RecyClass concludes that UPM Raflatac 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology as per current market conditions and knowledge, is fully compatible with the existing European industrial recycling processes for coloured PE flexibles. The plastic generated by the recycling process may be used in high quality applications such as PE blown films up to 25 %³.

In regard to RecyClass Recyclability Certification, the present full compatibility with coloured PE flexibles recycling delivered to 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology, means that a coloured package based on PE film containing this technology, as mentioned in the aforementioned conditions, will not be penalised with a recyclability class downgrade. Nevertheless, the amount of recyclable PE will impact the final recyclability class obtained during Recyclability Certification and should be kept above 95 % or 90 % in the final packaging to maximise chances to get a Recyclability Certificate with a Class A or B, respectively⁴. Also, it is noteworthy that the presence of additional packaging features, like inks or barrier material, could additionally impact the certification process.

Under the condition that the label is transparent and non-printed, the 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology is also considered to be fully compatible with natural PE flexibles recycling. The technology must only be designed according to the conditions previously mentioned, and be transparent. A small amount of inks can be accepted if it is compliant with the corresponding RecyClass Design for Recycling Guidelines⁵.

² [Design for Recycling Guidelines - RecyClass](#)

³ Technology tested according to the RecyClass [Recyclability Evaluation Protocol for PE films](#)

⁴ [RecyClass Recyclability Certification](#)

⁵ [Design for Recycling Guidelines - RecyClass](#)

About RecyClass

RecyClass is a non-profit, cross-industry initiative advancing recyclability, bringing transparency to the origin of plastic waste and establishing a harmonized approach toward recycled plastic calculation & traceability in Europe. RecyClass develops Recyclability Evaluation Protocols and scientific testing methods for innovative plastic packaging materials which serve as the base for the Design for Recycling Guidelines and the RecyClass Online Tool. RecyClass established Recyclability Certifications for plastic packaging, Recycling Process Certification and Recycled Plastics Traceability Certification for plastic products.

RecyClass – Plastic Future is Circular

Follow the latest news on RecyClass channels: [LinkedIn](#) | [Twitter](#) | [YouTube](#)

Contact : Jean-Emile.Potaufoux@plasticsrecyclers.eu, www.recyclclass.eu

Annex I



Figure 1. 'RP37 MULTIPURPOSE ACRYLIC EMULSION' technology by UPM Raflatac.